



FEP 200C 300v UL 1332

UL/CSA Approved Lead Wire
 300 Volts, 200° C, #24 AWG - #10 AWG
 UL Style: 1332 CSA:AWM Class 1 Group A/B



DESCRIPTION:

Conductor:
 Solid or Stranded tinned, annealed copper per ASTM B33.

Sizes:
 #24 AWG - #10 AWG

Insulation:
 Extruded FEP fluoropolymer jacket.

Colors available upon request.
 * NPC Conductor required for 200°C Rating

APPROVALS:

UL Style 1332. CSA:AWM Class 1 Group A/B

APPLICATIONS:

Used for wiring of electric heaters, appliances, thermocouples, gas igniters, electrical and electronic components, and other products up to 200° C. Provides excellent resistance to gasoline, oil, moisture, and acids.

AWG	Stranding	Insulation Thickness	Overall Diameter	Weight lbs/k ft	Temp Rating	UL Style
24*	7/.008	0.013	0.060	4	200°C	1332
22*	7/.010	0.013	0.055	5	200°C	1332
20*	7/.0126	0.013	0.065	7	200°C	1332
18	7/.0159	0.013	0.075	9	200°C	1332
16	7/.0192	0.013	0.085	12	200°C	1332
14	7/.0242	0.013	0.095	16	200°C	1332
12	19/.0179	0.013	0.115	23	200°C	1332
10	37/.0159	0.013	0.145	33	200°C	1332

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

P.O. Box 2005 - 160 South Hartman Street - York, PA 17403
 (717) 845-5100 - (800) 645-9473 - Fax (717) 848-6859