



PFA 250C 300v UL 1726

UL/CSA Approved Lead Wire
300 Volts, 250° C, #24 AWG - #4/0 AWG
UL Style: 1726 CSA:AWM Class 1 Group A/B



DESCRIPTION:

Conductor:
Stranded, annealed nickel plated copper per
ASTM B33.

Sizes:
#24 AWG - #4/0 AWG

Insulation:
Extruded PFA fluoropolymer jacket.

Colors available upon request.

APPROVALS:

UL Style 1726. CSA:AWM Class 1 Group
A/B

APPLICATIONS:

Used for wiring of electric heaters,
appliances, thermocouples, gas igniters,
electrical and electronic components and
other products up to 250° C. Provides
excellent resistance to gasoline, oil,
moisture, and acids.



AWG	Stranding	Insulation Thickness	Overall Diameter	Weight lbs/k ft	Temp Rating	UL Style
24	7/.008	0.013	0.05	4	250°C	1726
22	10/.0058	0.013	0.055	5	250°C	1726
20	19/.0073	0.013	0.065	7	250°C	1726
18	19/.0092	0.013	0.075	10	250°C	1726
16	19/.0117	0.013	0.085	13	250°C	1726
14	19/.0147	0.013	0.110	16	250°C	1726
12	19/.0185	0.013	0.115	22	250°C	1726
10	37/.0159	0.013	0.145	32	250°C	1726
8	133/.0111	0.020	0.210	64	250°C	1726
6	133/.0141	0.020	0.250	97	250°C	1726
4	133/.0177	0.030	0.325	160	250°C	1726
2	133/.0223	0.030	0.395	235	250°C	1726
1	259/.0177	0.045	0.470	320	250°C	1726
1/0	259/.0202	0.045	0.515	400	250°C	1726
2/0	259/.0229	0.045	0.570	495	250°C	1726
4/0	259/.0286	0.045	0.690	730	250°C	1726

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

P.O. Box 2005 - 160 South Hartman Street - York, PA 17403
 (717) 845-5100 - (800) 645-9473 - Fax (717) 848-6859