



SFF-2 SEWF-2 150C 600v

Silicone Rubber Glass Braid Fixture Wire - Flexible Stranded Conductors
600 Volts, 150° C, #18 AWG - #10 AWG



DESCRIPTION:

Conductor:

Flexible stranded tinned, annealed copper per ASTM B33.

Sizes:

#18 AWG - #10 AWG

Insulation:

Silicone Rubber. A fiberglass braid jacket is applied over the insulation, then treated with a high temperature lacquer finish.

Colors available upon request.

APPROVALS:

18 AWG – 14 AWG are UL approved as fixture wire (SFF-2). UL appliance wire approvals as listed. CSA approved as equipment wire (SEWF-2) as well as appliance wire.

APPLICATIONS:

Used as motor lead wire or the wiring of electrical equipment and lighting fixtures.

AWG	Stranding	Insulation Thickness	Fiberglass Braid	Overall Diameter	Weight lbs/k ft	Temp Rating	UL Style
18	16/.0100	0.030	.005	0.121	11	150°C	3070/SFF-2/SEWF-2
16	26/.0100	0.030	.005	0.132	16	150°C	3070/SFF-2/SEWF-2
14	41/.0100	0.030	.005	0.150	22	150°C	3070/SFF-2/SEWF-2
12	65/.0100	0.030	.005	0.170	31	150°C	3070
10	105/.0100	0.045	.005	0.227	52	150°C	3101

Dimensions and weights shown are nominal, subject to industry tolerances. Dimensions and weights for other cable configurations are available upon request.

P.O. Box 2005 - 160 South Hartman Street - York, PA 17403
(717) 845-5100 - (800) 645-9473 - Fax (717) 848-6859